

teXXmo *your ticket to mobility!*

KALEO DT315CR



teXXmo

Mobile Solution
GmbH & Co. KG
Otto-Lilienthal-Str. 36
D-71034 Böblingen

fon +49 70 31-71 48 50
fax +49 70 31-71 48 49

www.teXXmo.com
info@teXXmo.com

KALEO DT315CR

System - System	
CPU <i>Prozessor</i>	Intel® Atom™ Quad Core, 1.44GHz (up to 1.92GHz)
RAM <i>Arbeitsspeicher</i>	4GB
Storage <i>Festplattenkapazität</i>	128GB Flash
Operating System <i>Betriebssystem</i>	Microsoft® Windows® 10 IoT Enterprise
Display <i>Bildschirm</i>	24.6 cm (9.7") LED-backlight screen with capacitive touch, anti-reflection outdoor viewable
Display Resolution <i>Bildschirmauflösung</i>	1024 x 768 (XGA)
Network <i>Netzwerk</i>	Wi-Fi 802.11ac, 2.4GHz/ 5GHz dual band, Bluetooth 4.0 LE
Trusted Platform Module <i>Trusted Platform Module</i>	TPM 1.2 support
Control Switch and Button <i>Tasten</i>	1 power button and 2 trigger buttons
Indicator <i>Anzeigen</i>	1 power/ battery status LED
Speaker <i>Lautsprecher</i>	Built-in speaker
SD Slot <i>SD-Kartenleser</i>	1 full size SD card slot
I/O Ports - Anschlüsse	
USB 3.0 Port <i>USB 3.0 Anschluss</i>	1
Audio Jack <i>Audio-Buchse</i>	1
Power-in <i>Stromanschluß</i>	1
Mechanical and Environmental - Umgebung	
AC/DC Adapter <i>Netzteil</i>	Input: 100 – 240V AC; Output: DC 12V, 3.5A
Battery Pack <i>Akkupack</i>	Hot swappable battery, 3.7V, 8800mAh
Enclosure <i>Gehäuse</i>	ABS + PC plastics and magnesium-aluminum alloy
Protective Grips <i>Schutzecken</i>	Rubber side-grips with handstrap
Dimensions (H x W x D) <i>Abmessungen (H x B x T)</i>	211.5 x 260 x 20.3 mm
Weight <i>Gewicht</i>	1.22 kg
Water and Dust Resistance <i>Schutz gegen Nässe u. Staub</i>	Protected against dust and water, IP52 front panel
Regulatory <i>Zertifizierungen</i>	FCC Class B, CE, RoHS compliant
Temperature <i>Temperatur</i>	Operation: 0 °C - 40 °C; Storage: -20°C – 60°C
Humidity <i>Luftfeuchtigkeit</i>	0% – 90% non-condensing
Options - Optionen	
Back Camera <i>Kamera hinten</i>	5M pixel
Barcode Scanner (2D) <i>Barcode Scanner (2D)</i>	2D barcode scanner; reads 1D also
MSR <i>Magnetkartenleser</i>	Single, double, or triple track; reads AAMVA, ISO bank (ISO 7811); supports unencrypted mode, TDES encryption with static/DUKPT, Remote Key Injection (RKI)



Desktop Cradle



Wall/Vehicle Cradle



X-Hand Strap



Battery Charger



Stylus



Shoulder Strap



Protective Foils



DC/DC-Adapter

teXXmo

Mobile Solution
GmbH & Co. KG
Otto-Lilienthal-Str. 36
D-71034 Böblingen

fon +49 70 31-71 48 50
fax +49 70 31-71 48 49

www.teXXmo.com
info@teXXmo.com